



120W Desktop Series Power Supply

Features:

- * Universal AC Input 100 - 240Vac
- * Output Voltage: 12-56Vdc
- * Regulated Output With Low Ripple Noise
- * Safety Agency Requirements and EMI/EMS Certified
- * Short Circuit, Over Voltage, Over Current & Over Temperature Protections



Input	
Voltage (Vac)	100-240
Maximum Current (Amp)	1.6
Line Frequency (Hz)	50-60
Configuration	IEC60320/C6(PSD Series), C14 (PS Series)

Output	
Load Regulation	+5% (Typical)
Ripple	1 - 2% Vp-p Max. for output voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Holding Time	10mS @ Full Load
Protection	Short Circuit, Over Voltage, Over Current & Over Temperature Protections
DC Cord	18AWG / 16AWG / 14AWG
Ferrite Core	Yes

Electrical	
Topology	Switching Flyback
Dielectric Withstand	3000 VAC Primary - Secondary
Leakage Current	3.5mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, NRCAN & GEMS Level VI Certified
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25 degree celsius by Telcordia SR-332

Environmental	
Operating Temperature	0 to +40 degree celsius
Storage Temperature	-20 to +80 degree celsius
Operating Relative Humidity	20 to 80% RH
Storage Relative Humidity	10 to 90% RH

Safety	
Certified with CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM	

PART NUMBER	OUTPUT VOLTAGE (Vdc)	OUTPUT CURRENT (Amp)	WATTAGE (W)
PS-1290APL05	12	9	108
PS-1290APL06	12	9	108
PS-1580APL05	15	8	120
PS-1580APL06	15	8	120
PS-1675APL05	16	7.5	120
PS-1675APL06	16	7.5	120
PS-1866APL05	18	6.6	120
PS-1866APL06	18	6.6	120
PS-1963APL05	19	6.3	120
PS-1963APL06	19	6.3	120
PS-2060APL05	20	6	120
PS-2060APL06	20	6	120
PS-2450APL05	24	5	120
PS-2450APL06	24	5	120
PS-3040APL05	30	4	120
PS-3040APL06	30	4	120
PS-4825APL05	48	2.5	120
PS-4825APL06	48	2.5	120
PS-5621APL05	56	2.1	120
PS-5621APL06	56	2.1	120