



GOLDEN PACIFIC ELECTRONICS, INC.

560 South Melrose Street

Placentia, CA 92870

Phone#: 714-993-6970

Fax#: 714-993-6023

www.gpelectronics.com

sales@gpelectronics.com

15W PXM Series Interchangeable Wall Plug

Features

- ◆ To provide wide AC voltage input 90VAC~264VAC;
- ◆ Protections: Short circuit/Over current/Over voltage;
- ◆ Meet energy star level V (V2.0).



Input Voltage Range	90 ~ 240VAC	Operation Temp	0°C ~ 40°C
Input Current	500mA	Storage Temp	- 20°C ~ 60°C
Average Efficiency	Meet energy star level V (V2.0)	Humidity	5% to 95% non condensing
Output Voltage Range	±5%	MTBF	50,000 hours at maximum load levels and an ambient temperature of 25°C (in correspondence with MIL-HDBK-217)
Low Standby Power	0.3W		
Safety Approval	cULus(ITE UL60950 & Medical UL60601), TUV-GS(ITE EN60950 & Medical EN60601, LED EN61347), CE, PSE, C-Tick, CCC(ITE GB4943)		
Dimensions	75mm (L) ; 46mm (W) ; 30.5mm (H)		
Applications	ITE Equipment Medical Device, Lamp		

Output data



Part Number	Voltage (V)	Current (A)	Ripple (mV)	V		Av. Eff. (%)
				115	230	Min
PXM-3620A	3.60	0.01-2.00	50	Y	Y	75.9
PXM-4020A	4.00	0.01-2.00	50	Y	Y	75.9
PXM-4220A	4.20	0.01-2.00	50	Y	Y	75.9
PXM-4520A	4.50	0.01-2.00	50	Y	Y	75.9
PXM-5020A	5.00	0.01-2.00	50	Y	Y	75.9
PXM-5220A	5.20	0.01-2.00	100	Y	Y	75.9
PXM-5520A	5.50	0.01-2.00	100	Y	Y	75.9
PXM-5920A	5.99	0.01-2.00	100	Y	Y	75.9
PXM-6020A	6.00	0.01-2.00	100	Y	Y	
PXM-6520A	6.50	0.01-2.00	100	Y	Y	
PXM-7017A	7.00	0.01-1.70	100	Y	Y	81
PXM-7515A	7.50	0.01-1.50	100	Y	Y	81
PXM-8015A	8.00	0.01-1.50	100	Y	Y	81
PXM-8514A	8.50	0.01-1.40	100	Y	Y	81
PXM-9014A	9.00	0.01-1.40	100	Y	Y	81
PXM-1014A	10.0	0.01-1.40	100	Y	Y	81
PXM-1013A	10.5	0.01-1.30	100	Y	Y	81
PXM-1212A	12.0	0.01-1.25	120	Y	Y	81
PXM-1310A	13.8	0.01-1.05	150	Y	Y	81
PXM-1510A	15.0	0.01-1.00	150	Y	Y	81
PXM-1685	16.0	0.01-0.85	200	Y	Y	81
PXM-1780	17.5	0.01-0.80	200	Y	Y	81
PXM-1880	18.0	0.01-0.80	200	Y	Y	81.3
PXM-1975	19.0	0.01-0.75	200	Y	Y	81.3
PXM-2075	20.0	0.01-0.75	200	Y	Y	81.3
PXM-2265	22.0	0.01-0.65	200	Y	Y	81.3
PXM-2365	23.0	0.01-0.65	200	Y	Y	81.3
PXM-2463	24.0	0.01-0.63	240	Y	Y	81.3