



200W Medical Series Desktop Power Supply

Features:

- * Universal AC Input 100 - 240Vac
- * Output Voltage: 12-48Vdc
- * Regulated Output With Low Ripple Noise
- * Safety Agency Requirements and EMI/EMS Certified
- * Short Circuit, Over Voltage, Over Current & Over Temperature Protections
- * 2 x MOPP (Means of Patient Protection)
- * Touch Current: < 100µA



Input	
Voltage (Vac)	100-240
Maximum Current (Amp)	0.9-2.5
Line Frequency (Hz)	50-60
Configuration	IEC60320/C6(PSD Series), C14 (PS Series)

Output	
Load Regulation	+5% (Typical)
Ripple	1 - 2% Vp-p Max. for output voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Holding Time	10mS @ Full Load
Protection	Short Circuit Protection; Over Voltage Protection; Over Current Protection; Over Temperature Protection
DC Cord	16AWG
Ferrite Core	No (Optional)

Electrical	
Topology	Switching Flyback
Dielectric Withstand	4000 VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	Energy Star Level V , ErP Stage 2 Certified
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2
EMS Immunity	Compliance to IEC60601-1-2
MTBF	300,000 Calculated Hours at 25 degree celsius by Telcordia SR-332

Environmental	
Operating Temperature	0 to +40 degree celsius
Storage Temperature	-20 to +80 degree celsius
Operating Relative Humidity	20 to 80% RH
Storage Relative Humidity	10 to 90% RH

Safety	
Certified with CB / UL / cUL / FCC / CE / T-mark(TUV) / PSE	

PART NUMBER	OUTPUT VOLTAGE (Vdc)	OUTPUT CURRENT (Amp)	WATTAGE (W)
PSM-12160APL05	12	16	192
PSM-12160APL06	12	16	192
PSM-18110ALP05	18	11	198
PSM-18110ALP06	18	11	198
PSM-19105APL05	19	10.5	199.5
PSM-19105APL06	19	10.5	199.5
PSM-2483APL05	24	8.3	199.2
PSM-2483APL06	24	8.3	199.2
PSM-4841APL05	48	4.1	200.16
PSM-4841APL06	48	4.1	200.16