



24W PXM Series Interchangeable Wall Plug

Features

- ◆ To provide wide AC voltage input 90VAC~264VAC;
- ◆ Protections:Short circuit/Over current/Over voltage;
- ◆ Comprehensive protection, which can effectively prevent the impact from 4KV lightning and AC surge;
- ◆ Meet energy star level V (V2.0)
- ◆ Green light LED indication.
- ◆ Meet 2 mopp medical certification



| | | | |
|----------------------|--|----------------|--|
| Input Voltage Range | 90 ~ 264VAC | Operation Temp | - 10°C ~ 45°C |
| Input Current | 800mA | Storage Temp | - 40°C ~ 70°C |
| Average Efficiency | Meet energy star level V (V2.0) and ERP | Humidity | 20% to 90% non condensing |
| Output Voltage Range | ±5% | MTBF | 50,000 hours at maximum load levels and an ambient temperature of 25°C (in correspondence with MIL-HDBK-217) |
| Low Standby Power | 0.3W | | |
| Safety Approval | Comply with cULus (ITE UL60950 & Medical UL60601) 、TUV-GS (ITE EN60950 & Medical EN60601) 、CE、CCC (ITE GB4943) | | |
| Dimensions | 90mm (L) ; 52mm (W) ; 36mm (H) | | |
| Applications | ITE Equipment, Medical Device | | |

Output data



| Part Number | Voltage (V) | Current (A) | Ripple (mV) | V 150 230 | | Av. Eff. (%) Min |
|-------------|-------------|-------------|-------------|--------------|---|------------------|
| PXM-3030A | 3.0 | 0.1-3.0 | 200 | N | N | |
| PXM-3330A | 3.3 | 0.1-3.0 | 200 | N | N | |
| PXM-3630A | 3.6 | 0.1-3.0 | 200 | N | N | |
| PXM-4030A | 4.0 | 0.1-3.0 | 200 | N | N | |
| PXM-4230A | 4.2 | 0.1-3.0 | 200 | N | N | |
| PXM-4530A | 4.5 | 0.1-3.0 | 200 | N | N | |
| PXM-4830A | 4.8 | 0.1-3.0 | 200 | N | N | |
| PXM-5030A | 5.0 | 0.1-3.0 | 200 | Y | Y | 76.42 |
| PXM-5230A | 5.2 | 0.1-3.0 | 200 | Y | Y | 76.71 |
| PXM-5530A | 5.5 | 0.1-3.0 | 200 | Y | Y | 77.13 |
| PXM-6030A | 6.0 | 0.1-3.0 | 200 | Y | Y | 80.41 |
| PXM-6530A | 6.5 | 0.1-3.0 | 200 | Y | Y | 80.92 |
| PXM-7030A | 7.0 | 0.1-3.0 | 200 | Y | Y | 81.39 |
| PXM-7530A | 7.5 | 0.1-3.0 | 200 | Y | Y | 81.82 |
| PXM-8026A | 8.0 | 0.1-2.66 | 200 | Y | Y | 81.47 |
| PXM-8526A | 8.5 | 0.1-2.66 | 200 | Y | Y | 81.85 |
| PXM-9026A | 9.0 | 0.1-2.66 | 200 | Y | Y | 82.23 |
| PXM-9824A | 9.8 | 0.1-2.44 | 200 | Y | Y | 82.23 |
| PXM-1024A | 10.0 | 0.1-2.40 | 200 | Y | Y | 82.23 |
| PXM-1022A | 10.5 | 0.1-2.28 | 200 | Y | Y | 82.23 |
| PXM-1220A | 12.0 | 0.1-2.00 | 200 | Y | Y | 82.23 |
| PXM-1219A | 12.6 | 0.1-1.90 | 200 | Y | Y | 82.23 |
| PXM-1318A | 13.0 | 0.1-1.84 | 200 | Y | Y | 82.23 |
| PXM-1317A | 13.8 | 0.1-1.73 | 200 | Y | Y | 82.23 |
| PXM-1516A | 15.0 | 0.1-1.60 | 200 | Y | Y | 82.23 |
| PXM-1615A | 16.0 | 0.1-1.50 | 200 | Y | Y | 82.23 |
| PXM-1614A | 16.5 | 0.1-1.45 | 200 | Y | Y | 82.23 |
| PXM-1813A | 18.0 | 0.1-1.33 | 200 | Y | Y | 82.23 |
| PXM-2012A | 20.0 | 0.1-1.20 | 200 | Y | Y | 82.23 |
| PXM-2210A | 22.0 | 0.1-1.09 | 200 | Y | Y | 82.23 |
| PXM-2310A | 23.0 | 0.1-1.04 | 200 | Y | Y | 82.23 |
| PXM-2410A | 24.0 | 0.1-1.00 | 200 | Y | Y | 82.23 |