



GOLDEN PACIFIC ELECTRONICS, INC.
 560 South Melrose Street
 Placentia, CA 92870
 Phone#: 714-993-6970
 Fax#: 714-993-6023
www.gpelectronics.com
sales@gpelectronics.com

8W PXM Series Interchangeable Wall Plug

Features

- ◆ Wide range of AC input voltage 90VAC~264VAC
- ◆ Protections against: short circuit/over current/over voltage
- ◆ Some of this series meet energy star level V (V2.0) (see the table below)



Input Voltage Range	90 ~ 264VAC	Operation Temperature	0°C ~ 40°C
Input Current	400mA	Storage Temperature	- 20°C ~ 60°C
Average Efficiency UE08WCP	Meets Energy Star level V (V2.0)	Humidity	5% to 95% non condensing
Output Voltage Range	±5%	MTBF	50,000 hours at full load at 25°C ambient, calculated per MIL-HDBK-217
Standby Power	0.3W		
Safety Standard	cULus(ITE UL60950 & Medical UL60601)、TUV-GS(ITE EN60950 & Medical EN60601)、CE Mark、PSE-JET(J60950)、CB、RCM		
Dimensions	72mm (L) ; 43mm (W) ; 29mm (H)		
Applications	Medical device And Information device.		

Output data



Part Number	Voltage (V)	Current (A)	Ripple (mV)	V		Av. Eff. (%) Min
				115	230	
PXM-3020A	3.0	0.1-2.00	150	N	N	
PXM-3320A	3.3	0.1-2.00	150	N	N	
PXM-4219A	4.2	0.1-1.90	150	N	N	
PXM-5016A	5.0	0.1-1.60	150	N	N	
PXM-5514A	5.5	0.1-1.45	150	N	N	
PXM-5714A	5.7	0.1-1.40	150	N	N	
PXM-6013A	6.0	0.1-1.33	150	Y	Y	75.31
PXM-6512A	6.5	0.1-1.23	150	Y	Y	75.31
PXM-7011A	7.0	0.1-1.13	150	Y	Y	75.31
PXM-7510A	7.5	0.1-1.05	150	Y	Y	75.31
PXM-8010A	8.0	0.1-1.00	150	Y	Y	75.31
PXM-8590	8.5	0.1-0.94	150	Y	Y	75.31
PXM-9088	9.0	0.1-0.88	150	Y	Y	75.31
PXM-1076	10.5	0.1-0.76	150	Y	Y	75.31
PXM-1266	12.0	0.1-0.66	150	Y	Y	75.31
PXM-1264	12.5	0.1-0.64	150	Y	Y	75.31
PXM-1357	13.8	0.1-0.57	150	Y	Y	75.31
PXM-1553	15.0	0.1-0.53	150	Y	Y	75.31
PXM-1844	18.0	0.1-0.44	150	Y	Y	75.31