



GOLDEN PACIFIC ELECTRONICS, INC.
560 South Melrose Street
Placentia, CA 92870
Phone#: 714-993-6970
Fax#: 714-993-6023
www.gpelectronics.com
sales@gpelectronics.com

8W Battery Charger



◆ Features

- .Universal AC input/Full range
- .Charging mode: 2 Stage charging
- .Class II power (without earth pin)
- .Protection: Short circuit/Over voltage/Over current

◆ General Specification (Please contact us for detail spec.)

AC input voltage range	90~264Vac 120~370Vdc
AC input current (Max.)	0.25A/100Vac
Line Regulation	±1%
Load Regulation	±5%
Over voltage protection	105%~135% rated output voltage
Over current protection	Hiccup mode, Auto recovery
Withstand voltage	I/P-O/P:3KVac, 1 minute
Working temperature	0~40°C
Safety standards	UL1310,EN60335
EMC standards	EN55014 class B, FCC part15 class B
Output cable	20# to 24# according to output current
Standard DC plug	5.5*2.1*12mm/C+, other types available



8W

Part Number	Voltage	Voltage	Current	Effi.
BC-4220A	4.2V	3.6~4.4V	0~2.0A	>70%
BC-5615A	5.6V	5.0~5.8V	0~1.5A	>70%
BC-7211A	7.2V	6.5~7.5V	0~1.1A	>70%
BC-8410A	8.4V	7.7~8.6V	0~1.0A	>80%
BC-1260	12.0V	11.0~14.7V	0~0.6A	>80%
BC-1650	16.8V	16.0~17.0V	0~0.5A	>80%
BC-2430	24.0V	22.0~29.7V	0~0.3A	>80%

Charging curve

